





Our engineers know that the market needs a lighting tower that is rugged, long lasting and safe. The X-BOX LED has been created beginning from these characteristics. It is the best solution to your needs and guarantees 5000 sqm of illuminated area. 22 units can be loaded on a standard truck. To all of this, we added the technology that allows for maximum fuel efficiency and reliability.







8,5m 1030Kg 340° 5000 sqm

220(l) - 0,55(l/h)

- Multi-directionally adjustable and tiltable floodlights
- 7 sections hydraulic vertical tower 8,5 m, 340° rotatable
- Standard light sensor for machine power on and off
- Galvanized metalworks
- 80 µm powder coating
- Very compact dimensions for easy handling & transportability, up to 22 units per truck
- Central lifting eye longitudinal and transversal forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine proteciton and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Fully bunded tank, 110%
- Certified wind stability up tp 110 km/h
- 4 extendable & height adjustable stabilizers
- On board levels for guidance during stabilization

## **APPLICATIONS**

Special events



Rural & hard to reach areas

Emergency response




- Construction & work sites
- Gas,oil & mining operations
- Military applications






Ease of transport and handling



22 **Units Per Truck** 



You can place 22 units on a single vehicle thanks to one of the compactest footprints on the market.



technical data

Model

Frequency (Hz)

Insulation class

Degree of protection


Single phase voltage Auxiliary outlets

Dimensions & weight	
Dimensions min. (mm)	1200x1200x2560
Dimensions max. (mm)	2390x2390x8500
Total weight without fuel	1030 Kg
Features	
Rotation	340°
Floodlights	4x320W
Lamps	LED
Options	Timer
Alternator	

Engine	
Model	Kubota Z482
Fuel	Diesel
r.p.m	1500
Tank capacity (I)	220
Consumption (l/h)	0,55
Running time (h)	400
Noise level (dBA) at 7m	65


\* May vary based on stock availability. However, a primary equivalent brand will be used

## Standard load delivery



1 kVA Units Per Truck

Illuminated area



5000 sqm

Synchronous

3,5 kVA - 230V

50

Н

IP23



## TRIME s.r.l.

Strada per Robecco, snc 20081 Cassinetta di Lugagnano (MI) - Italy Tel. +39 02 942 1724 Sales Dept. +39 0382 406 252 www.trime.it - info@trime.it