



OMEGA
PLATFORMS

400-SERIES

Track scissor with levelling capabilities

- » Up to 10,5 m working height.
- » Standard double extension decks - up to 5 m extended.
- » Easy levelling capabilities, side - side / fore - aft.
- » Closed hydraulic circuit for drive operations by means of two individual piston pumps.
- » All electrical, hydraulic and diesel components are in closed compartments.
- » Guardrails are easily detachable.
- » Fully proportional drive control, with double joystick controllers.

405TS/408TS Track scissor

Specifications

	405TS	408TS
Max. working height	10,5 m	10,5 m
Max. platform height	8,5 m	8,5 m
Stowed height (top guardrails)	2,9 m	2,9 m
Stowed height (rails detached)	2,0 m	2,0 m
Width	1,6 m	1,6 m
Length - stowed	3,0 m	3,0 m
Track length	2,65 m	2,65 m
Track base	1,6 m	1,6 m
Ground clearance	33 cm	33 cm
Platform length - retracted	3,0 m	3,0 m
Platform length - extended	5,0 m	5,0 m
Lifting capacity	500 kg	800 kg
Max. load roll-out decks	250 kg	250 kg
Drive speed stowed	2,5 km/h	2,5 km/h
Gradeability	40%	40%
Weight	4.400 kg	4.600 kg
Engine	Kubota D1505	Kubota D1505
Levelling capabilities	5° side to side / 3° fore to aft Controls by manual - and by Auto-levelling feature	

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.



www.omegasales.eu

Standard features

- » Up to 10,5 m working height.
- » Auto and manual levelling - 5° side / side & 3° fore / aft.
- » Removable upper controls.
- » Double extension decks.
- » Fully proportional drive and lift control.
- » Easy maintenance access to mechanical, electrical and diesel components without raising platform or swinging out trays.
- » CE compliant.
- » Power full diesel engine - Kubota D1105.



Optional features

- » Hydraulic powered generator 220Vac, up to 6 kW.
- » DC / AC convertor for 220Vac supply, up to 2 kW.
- » Non-marking tracks.
- » Custom colours.
- » Radiographic remote controls.

Leemidden 21
2678 ME De Lier
The Netherlands

+ 31 174 - 525 990
sales@omegasales.eu